



2017 Bearcat 7000 XT GS



AVAILABLE COLORS



Black

Engine Specifications

Type	4-stroke
Displacement (cc)	1049
Cooling	Liquid
Cylinders	3
Bore x Stroke (mm)	82 x 62.2
Lubrication	Dry sump
Ignition	Digital controlled coil induction
Engine Stator Output	515 Watts
Fuel Delivery	Electronic Fuel Injected (EFI)
Exhaust	3-into-1 stainless steel pipe with stainless steel muffler
Fuel Capacity gal. (l)	14.7 (55.65)
Oil System Capacity qt. (l)	3.9 (3.69)
Coolant System Capacity qt. (l)	5.8 (5.49)
Minimum Octane	87

Suspension Specifications

Front Suspension	Arctic Race Suspension with sway bar
Ski Shocks	Arctic Cat IFP 1.5
Front Travel in. (cm)	9 (22.86)
Rear Suspension	XTRA-ACTION Rear Suspension with adjustable torsion springs, fiberglass overload springs and Torque-Sensing Link rear arm
Front Track Shock	Arctic Cat IFP 1.5
Rear Track Shock	Arctic Cat IFP 1.5
Rear Travel in. (cm)	13 (32.02)

Dimensions Specifications

Chassis Overall Length in. (cm)	133 (337.82)
Chassis Overall Width in. (cm)	50 (127)
Chassis Overall Height in. (cm)	58 (147.32)
Track Type	Std
Track Width in. (cm)	20 (50.08)
Track Length in. (cm)	154 (391.16)
Lug in. (cm)	1.375 (3.49)
Pitch in. (cm)	2.86 (7.26)
Ski Stance in. (cm)	37.5-43.5 (95.25-110.49) Adjustable
Ski Type / Width in. (cm)	ProUte - 10 (25.4)/8 (20.32)

Instrumentation Specifications

Type of Gauge	Power Sport
Speedometer	Digital
Tachometer	Digital
Odometer	Digital
Fuel	Digital
Oil	Indicator Light
Coolant	Digital/Indicator Light
Clock	Digital
Battery Voltage	Digital
Altimeter	Digital
Hours	Digital

Feature Specifications

12V Outlet	Standard
3,000 lb.(1 360.8 kg) Winch with Receiver Mount	Standard
Actuator Switches (2)	Standard
Backup Light	Standard
Beacon Light	Standard
Electric Start	Standard
Floodlight	Standard
Front Bumper	Heavy Duty
Hand & Thumb Warmers	Standard
Hand Guards	Accessory
Headlights	Dual halogen 2-bulb
Heated Drivers Seat	Accessory
Heated Passenger Seat	Accessory
Heavy-Duty Rear Bumper	Standard
Ice Scratchers	Accessory
Light Bar	Standard
Lightweight Brake Disc	Accessory
Mirrors	Standard
Mountain Strap	Standard
Passenger Footrests	Accessory
Passenger Hand Warmers	Accessory
Passenger Seat	Accessory
Passenger Wind Deflectors	Accessory
Radiator	Standard
Rear Accessory Outlet	Accessory
Rear Rack	Accessory
Rocker Switch	Standard
Roller Fairlead & 50 ft.(15.24 m) of Steel Cable	Standard
Seat	ProUtility
Sno Pro Brake Lever	Accessory
Steering	4.5 in. (11.43 cm) riser with adjustable handlebar & grab strap
Tether Switch	Accessory
Tow Hitch	Pintle
Tunnel Rails	Standard
Visor Plug-ins	Accessory
Windshield	19 in. (48.26 cm) High-height

Powertrain Specifications

Drive Clutch	TEAM Rapid Response
Driven Clutch	TEAM Rapid Reaction BOSS
Drive System	Wide Range 3 Speed (WR3)
Brakes	Race radial master cylinder hydraulic brake

Runner Type	Dual split runner w/carbide	Clutch Calibration ft. (m)	0-5,000 (0-1,524)
		Gearing	WR3
		Reverse	Shift lever

Specifications Subject To Change

All rights reserved. Cobra,™ Hacksaw™ and Ripsaw™ are trademarks of Camoplast Inc. Diamond Direct Drive™ is a trademark of Black Diamond, Inc. FOX EVOL,™ FOX FLOAT™ and FOX Zero Pro are registered trademarks of FOX Racing Shox. ACT™ Arctic Cat, Arctic Drive System,™ Arctic Race Suspension,™ ARS,™ AWS,™ Bearcat, C-TEC2,™ C-TEC4,™ CatMaster, Cat to the Core,™ Cross Country,™ El Tigré, FasTrack, High Country,™ Lynx, Pantera, Power Claw,™ ProClimb,™ ProCross,™ ProTour,™ RIDEMORE,™ Share Our Passion,™ Slide-Action Rear Suspension,™ Sno Pro, SpeedRack, Torque Control Link,™ Twin Spar,™ World's Fastest Snowmobiles,™ XT,™ Z1™ and ZR are trademarks or registered trademarks of Arctic Cat Inc. Arctic Cat Sales Inc. is not a successor of Arctic Enterprises, Inc. ©2014 Arctic Cat Sales Inc., 601 Brooks Avenue South, Thief River Falls, MN 56701.

At Arctic Cat, we're always improving our snowmobiles to provide the best performance and experience. That's why the specifications for 2015 model Arctic Cat snowmobiles are subject to change without notice. See your dealer for details.

*MSRP excludes tax, license, registration, destination charge of \$400 and dealer setup. Dealer prices may vary.