



2017 Lynx 2000 ES



AVAILABLE COLORS



Black

Engine Specifications

Type	2-Stroke
Displacement (cc)	565
Cooling	Fan
Cylinders	2
Bore x Stroke (mm)	73.8x66
Lubrication	Oil injection
Ignition	Digitally Controlled CDI
Engine Stator Output	210 Watts
Fuel Delivery	2 x VM 34 Carburetors
Exhaust	Tuned pipe and muffler
Fuel Capacity gal. (l)	10.8 (40.88)
Oil System Capacity qt. (l)	4.2 (3.97)
Coolant System Capacity qt. (l)	N/A
Minimum Octane	87

Suspension Specifications

Front Suspension	AWS VII with sway bar
Ski Shocks	Hydraulic twin tube shocks
Front Travel in. (cm)	9.5 (24.13)
Rear Suspension	SLIDE-ACTION Rear Suspension, Torque-Sensing Link rear arm and adjustable torsion springs
Front Track Shock	Hydraulic twin tube
Rear Track Shock	Hydraulic twin tube
Rear Travel in. (cm)	13.5 (34.29)

Dimensions Specifications

Chassis Overall Length in. (cm)	118 (299.72)
Chassis Overall Width in. (cm)	48 (121.92)
Chassis Overall Height in. (cm)	49 (124.46)
Track Type	Challenger
Track Width in. (cm)	15 (38.1)
Track Length in. (cm)	129 (327.66)
Lug in. (cm)	1.0 (2.54)
Pitch in. (cm)	2.52 (6.40)
Pitch in. (cm)	43 (109.22)
Ski Type / Width in. (cm)	ProCross - 6 (15.24)
Runner Type	Dual split runner w/carbide

Instrumentation Specifications

Type of Gauge	Digital Analog
Speedometer	Digital/Analog
Tachometer	Digital/Analog
Odometer	Digital
Fuel	Digital
Oil	Indicator Light
Coolant	NA
Clock	Digital
Battery Voltage	NA
Altimeter	NA
Hours	Digital

Feature Specifications

12V Outlet	NA
3,000 lb.(1 360.8 kg) Winch with Receiver Mount	NA
Actuator Switches (2)	NA
Adjustable Backrest	NA
Auxiliary Gas Tank 4.3 gal.(16.28 l)	NA
Backup Light	NA
Beacon Light	NA
Electric Start	Standard
Floodlight	NA
Front Bumper	Standard
Goggle Holder	Accessory
Hand & Thumb Warmers	Standard
Hand Guards	Accessory
HCR-type Heat Exchanger	NA
Headlights	Dual halogen 4-bulb
Heated Drivers Seat	NA
Heated Passenger Seat	NA
Heavy-Duty Rear Bumper	NA
Ice Scratchers	Accessory
Light Bar	NA
Lightweight Brake Disc	NA
Locking Detachable Storage Cases	NA
Mirrors	Accessory
Mountain Strap	Accessory
Passenger Footrests	NA
Passenger Hand Warmers	NA
Passenger Seat	NA
Passenger Wind Deflectors	NA
Radiator	NA
Rear Accessory Outlet	NA
Rear Rack	Accessory
Rear Storage	Accessory
Rocker Switch	NA
Roller Fairlead & 50 ft.(15.24 m) of Steel Cable	NA
Safety Flag	NA
Seat	Trail
Side Panel Wind Deflectors	NA
Sno Pro Brake Lever	NA
Steering	Fixed with adjustable handlebar
Tether Switch	Accessory
Tow Hitch	Accessory
Tunnel Flare	NA
Tunnel Rails	NA
Underseat Storage	NA

Visor Plug-ins	Accessory
Windshield	10 in. (25.4 cm) Mid-height

Powertrain Specifications

Drive Clutch	Arctic 6 post (rpm sensing)
Driven Clutch	10.75 in. dia. Arctic (roller cam)
Drive System	ACT Diamond Direct Drive
Brakes	Axial master cylinder hydraulic brake / disc on driveshaft
Clutch Calibration ft. (m)	0-5,000 (0-1,524)
Gearing	57/63
Chain Pitch	NA
Reverse	Push-button Engine

Specifications Subject To Change

All rights reserved. Cobra,™ Hacksaw™ and Ripsaw™ are trademarks of Camoplast Inc. Diamond Direct Drive™ is a trademark of Black Diamond, Inc. FOX EVOL,™ FOX FLOAT™ and FOX Zero Pro are registered trademarks of FOX Racing Shox. ACT™ Arctic Cat, Arctic Drive System,™ Arctic Race Suspension,™ ARS,™ AWS,™ Bearcat, C-TEC2,™ C-TEC4,™ CatMaster, Cat to the Core,™ Cross Country,™ El Tigré, FasTrack, High Country,™ Lynx, Pantera, Power Claw,™ ProClimb,™ ProCross,™ ProTour,™ RIDEMORE,™ Share Our Passion,™ Slide-Action Rear Suspension,™ Sno Pro, SpeedRack, Torque Control Link,™ Twin Spar,™ World's Fastest Snowmobiles,™ XT,™ Z1™ and ZR are trademarks or registered trademarks of Arctic Cat Inc. Arctic Cat Sales Inc. is not a successor of Arctic Enterprises, Inc. ©2014 Arctic Cat Sales Inc., 601 Brooks Avenue South, Thief River Falls, MN 56701.

At Arctic Cat, we're always improving our snowmobiles to provide the best performance and experience. That's why the specifications for 2015 model Arctic Cat snowmobiles are subject to change without notice. See your dealer for details.

*MSRP excludes tax, license, registration, destination charge of \$400 and dealer setup. Dealer prices may vary.