




2017 Lynx 2000 LT ES



AVAILABLE COLORS



Black

Engine Specifications

Type	2-stroke
Displacement (cc)	565
Cooling	Fan
Cylinders	2
Bore x Stroke (mm)	73.8 x 66
Lubrication	Oil injection
Ignition	CDI
Engine Stator Output	210 Watts
Fuel Delivery	2 x VM 34 Carburetors
Exhaust	Tuned pipe and muffler
Fuel Capacity gal. (l)	10.8 (40.88)
Oil System Capacity qt. (l)	4.2 (3.97)
Coolant System Capacity qt. (l)	N/A
Minimum Octane	87

Suspension Specifications

Front Suspension	AWS VII with sway bar
Ski Shocks	Hydraulic twin tube shocks
Front Travel in. (cm)	9.5 (24.13)
Rear Suspension	SLIDE-ACTION Rear Suspension, coupling blocks, Torque-Sensing Link rear arm, adjustable torsion springs and fiberglass overload springs
Front Track Shock	Hydraulic twin tube
Rear Track Shock	Hydraulic 2.0 twin tube
Rear Travel in. (cm)	13.3 (33.78)

Dimensions Specifications

Chassis Overall Length in. (cm)	131 (322.74)
Chassis Overall Width in. (cm)	48 (121.92)
Chassis Overall Height in. (cm)	53 (134.62)
Track Type	Challenger
Track Width in. (cm)	15 (38.1)
Track Length in. (cm)	144 (365.76)
Lug in. (cm)	1.0 (2.54)
Pitch in. (cm)	2.52 (6.40)
Ski Stance in. (cm)	43 (109.22)
Ski Type / Width in. (cm)	ProTour -6 (15.24)
Runner Type	Dual split runner w/carbide

Instrumentation Specifications

Type of Gauge	Digital Analog
Speedometer	Digital/Analog
Tachometer	Digital/Analog
Odometer	Digital
Fuel	Digital
Oil	Indicator Light
Clock	Digital
Hours	Digital

Feature Specifications

Adjustable Backrest	Standard
Electric Start	Standard
Front Bumper	Standard
Goggle Holder	Accessory
Hand & Thumb Warmers	Standard
Hand Guards	Accessory
Headlights	Dual halogen 4-bulb
Ice Scratchers	Accessory
Mirrors	Accessory
Mountain Strap	Accessory
Passenger Footrests	Standard
Passenger Seat	Standard
Passenger Wind Deflectors	Accessory
Rear Rack	Standard
Rear Storage	Accessory
Seat	Tour
Steering	Adjustable handlebar
Tow Hitch	Accessory
Tunnel Rails	Standard
Windshield	13 in. (32.02 cm) Mid-height

Powertrain Specifications

Drive Clutch	Arctic 6 post (rpm sensing)
Driven Clutch	10.4 in. dia. Arctic (roller cam)
Drive System	ACT Diamond Direct Drive
Brakes	Axial master cylinder hydraulic brake / disc on driveshaft
Clutch Calibration ft. (m)	0-5,000 (0-1,524)
Gearing	54/66
Reverse	Push-button Engine

Specifications Subject To Change

All rights reserved. Cobra,™ Hacksaw™ and Ripsaw™ are trademarks of Camoplast Inc. Diamond Direct Drive™ is a trademark of Black Diamond, Inc. FOX EVOL,™ FOX FLOAT™ and FOX Zero Pro are registered trademarks of FOX Racing Shox. ACT™ Arctic Cat, Arctic Drive System,™ Arctic Race Suspension,™ ARS,™ AWS,™ Bearcat, C-TEC2,™ C-TEC4,™ CatMaster, Cat to the Core,™ Cross Country,™ El Tigré, FasTrack, High Country,™ Lynx,

Pantera, Power Claw,™ ProClimb,™ ProCross,™ ProTour,™ RIDEMORE,™ Share Our Passion,™ Slide-Action Rear Suspension,™ Sno Pro, SpeedRack, Torque Control Link,™ Twin Spar,™ World's Fastest Snowmobiles,™ XT,™ Z1™ and ZR are trademarks or registered trademarks of Arctic Cat Inc. Arctic Cat Sales Inc. is not a successor of Arctic Enterprises, Inc. ©2014 Arctic Cat Sales Inc., 601 Brooks Avenue South, Thief River Falls, MN 56701.

At Arctic Cat, we're always improving our snowmobiles to provide the best performance and experience. That's why the specifications for 2015 model Arctic Cat snowmobiles are subject to change without notice. See your dealer for details.

*MSRP excludes tax, license, registration, destination charge of \$400 and dealer setup. Dealer prices may vary.