



2017 XF 7000 CrossTour



AVAILABLE COLORS



Orange

Engine Specifications

Type	4-stroke
Displacement (cc)	1049
Cooling	Liquid
Cylinders	3
Bore x Stroke (mm)	82 x 62.2
Lubrication	Dry sump
Ignition	Digital controlled coil induction
Engine Stator Output	515 Watts
Fuel Delivery	Electronic Fuel Injected (EFI)
Exhaust	3-into-1 stainless steel pipe with stainless steel muffler
Fuel Capacity gal. (l)	10.7 (40.50) + 4.3 (16.3) Auxiliary
Oil System Capacity qt. (l)	4.1 (3.88)
Coolant System Capacity qt. (l)	4.8 (4.54)
Minimum Octane	87

Suspension Specifications

Front Suspension	Arctic Race Suspension with sway bar
Ski Shocks	Arctic Cat IFP 1.5
Front Travel in. (cm)	10 (25.4)
Rear Suspension	SLIDE-ACTION Rear Suspension, coupling blocks, Torque-Sensing Link rear arm and adjustable torsion springs
Front Track Shock	Arctic Cat IFP 1.5
Rear Track Shock	Arctic Cat IFP 1.5
Rear Travel in. (cm)	13.5 (34.29)

Dimensions Specifications

Chassis Overall Length in. (cm)	127 (322.58)
Chassis Overall Width in. (cm)	48 (121.92)
Chassis Overall Height in. (cm)	52 (132.08)
Track Type	Ripsaw
Track Width in. (cm)	15 (38.1)
Track Length in. (cm)	146 (370.84)
Lug in. (cm)	1.25 (3.18)
Pitch in. (cm)	2.86 (7.26)
Ski Stance in. (cm)	42-43 (106.68-109.22) Adjustable
Ski Type / Width in. (cm)	ProCross - 6 (15.24)
Runner Type	Dual split runner w/carbide

Instrumentation Specifications

Type of Gauge	Deluxe Digital
Speedometer	Digital/Analog
Tachometer	Digital/Analog
Odometer	Digital
Fuel	Digital
Oil	Indicator Light
Coolant	Digital/Indicator Light
Clock	Digital
Battery Voltage	Digital
Altimeter	Digital
Hours	Digital

Feature Specifications

12V Outlet	Standard
Auxiliary Gas Tank 4.3 gal.(16.28 l)	Standard
Electric Start	Standard
Front Bumper	Standard
Goggle Holder	Accessory
Hand & Thumb Warmers	Standard
Hand Guards	Accessory
Headlights	Dual halogen 2-bulb
Heated Drivers Seat	Standard
Heated Passenger Seat	Accessory
Ice Scratchers	Accessory
Lightweight Brake Disc	Accessory
Locking Detachable Storage Cases	Accessory
Mirrors	Standard
Mountain Strap	Accessory
Passenger Footrests	Accessory
Passenger Hand Warmers	Accessory
Passenger Seat	Accessory
Passenger Wind Deflectors	Accessory
Radiator	Standard
Rear Accessory Outlet	Standard
Rear Storage	Compartment
Seat	ProTour
Side Panel Wind Deflectors	Accessory
Sno Pro Brake Lever	Accessory
Steering	5.5 in. (13.97 cm) riser with adjustable handlebar
Tether Switch	Accessory
Tow Hitch	Accessory
Visor Plug-ins	Standard
Windshield	11 in. (27.94 cm) Mid-height

Powertrain Specifications

Drive Clutch	TEAM Rapid Response
Driven Clutch	TEAM Rapid Reaction BOSS
Drive System	Arctic Drive System
Brakes	Race radial master cylinder hydraulic brake
Clutch Calibration ft. (m)	0-5,000 (0-1,524)
Gearing	21/49
Chain Pitch	90
Reverse	Push-button

Specifications Subject To Change

All rights reserved. Cobra,™ Hacksaw™ and Ripsaw™ are trademarks of Camoplast Inc. Diamond Direct Drive™ is a trademark of Black Diamond, Inc. FOX' EVOL,™ FOX FLOAT' and FOX' Zero Pro are registered trademarks of FOX Racing Shox. ACT™ Arctic Cat, Arctic Drive System,™ Arctic Race Suspension,™ ARS,™ AWS,™ Bearcat, C-TEC2,™ C-TEC4,™ CatMaster, Cat to the Core,™ Cross Country,™ El Tigré, FasTrack, High Country,™ Lynx,

Pantera, Power Claw,[™] ProClimb,[™] ProCross,[™] ProTour,[™] RIDEMORE,[™] Share Our Passion,[™] Slide-Action Rear Suspension,[™] Sno Pro, SpeedRack, Torque Control Link,[™] Twin Spar,[™] World's Fastest Snowmobiles,[™] XT,[™] Z1[™] and ZR are trademarks or registered trademarks of Arctic Cat Inc. Arctic Cat Sales Inc. is not a successor of Arctic Enterprises, Inc. ©2014 Arctic Cat Sales Inc., 601 Brooks Avenue South, Thief River Falls, MN 56701.

At Arctic Cat, we're always improving our snowmobiles to provide the best performance and experience. That's why the specifications for 2015 model Arctic Cat snowmobiles are subject to change without notice. See your dealer for details.

*MSRP excludes tax, license, registration, destination charge of \$400 and dealer setup. Dealer prices may vary.