



2017 XF 9000 Cross Country Limited (137)



AVAILABLE COLORS



Black

Engine Specifications

Type	4-stroke
Displacement (cc)	998
Cooling	Liquid
Cylinders	3-Turbocharged
Bore x Stroke (mm)	80 x 66.2
Lubrication	Dry sump
Ignition	Digital controlled coil induction
Engine Stator Output	545 Watts
Fuel Delivery	Electronic Fuel Injected (EFI)
Exhaust	Turbocharger with stainless steel muffler
Fuel Capacity gal. (l)	9.9 (37.48)
Oil System Capacity qt. (l)	3.25 (3.08)
Coolant System Capacity qt. (l)	5.7 (5.39)
Minimum Octane	91

Suspension Specifications

Front Suspension	Arctic Race Suspension with sway bar
Ski Shocks	FOX 1.5 ZERO QS3
Front Travel in. (cm)	9 (22.86)
Rear Suspension	SLIDE-ACTION Rear Suspension with tri-hub rear axle system, coupling blocks, Torque-Sensing Link rear arm and adjustable torsion springs
Front Track Shock	Arctic Cat IFP 1.5
Rear Track Shock	FOX 2.0 ZERO QS3
Rear Travel in. (cm)	13.5 (34.29)

Dimensions Specifications

Chassis Overall Length in. (cm)	131 (322.74)
Chassis Overall Width in. (cm)	45.5-49.5 (115.57-125.73)
Chassis Overall Height in. (cm)	50 (127)
Track Type	Backcountry X
Track Width in. (cm)	15 (38.1)
Track Length in. (cm)	137 (347.98)
Lug in. (cm)	1.75 (4.45)
Pitch in. (cm)	3.00 (7.62)
Ski Stance in. (cm)	42-43 (106.68-109.22) Adjustable
Ski Type / Width in. (cm)	ProCross - 6 (15.24)
Runner Type	Single runner w/carbide

Instrumentation Specifications

Type of Gauge	Deluxe Digital
Speedometer	Digital
Tachometer	Digital
Odometer	Digital
Fuel	Digital
Oil	Indicator Light
Coolant	Digital/Indicator Light
Clock	Digital
Battery Voltage	Digital
Altimeter	Digital
Hours	Digital

Feature Specifications

12V Outlet	Standard
Electric Start	Standard
Front Bumper	Standard
Goggle Holder	Accessory
Hand & Thumb Warmers	Standard
Hand Guards	Accessory
Headlights	LED w/ accent light
Heated Drivers Seat	Standard
Ice Scratchers	Accessory
Lightweight Brake Disc	Accessory
Mirrors	Accessory
Mountain Strap	Standard
Rear Rack	Standard
Rear Storage	Tunnel Bag
Seat	Mountain
Side Panel Wind Deflectors	Accessory
Sno Pro Brake Lever	Accessory
Steering	5.5 in. (13.97 cm) riser with adjustable handlebar
Tether Switch	Accessory
Tow Hitch	Accessory
Tunnel Flare	Accessory
Visor Plug-ins	Accessory
Windshield	5.5 in. (13.97 cm) Race-height

Powertrain Specifications

Drive Clutch	TEAM Rapid Response II
Driven Clutch	TEAM Rapid Reaction BOSS
Drive System	Arctic Drive System
Brakes	Race radial master cylinder hydraulic brake
Clutch Calibration ft. (m)	0-5,000 (0-1,524)
Gearing	22/48
Chain Pitch	90
Reverse	Push-button

Specifications Subject To Change

All rights reserved. Cobra,[™] Hacksaw[™] and Ripsaw[™] are trademarks of Camoplast Inc. Diamond Direct Drive[™] is a trademark of Black Diamond, Inc. FOX[®] EVOL,[™] FOX FLOAT[™] and FOX Zero Pro are registered trademarks of FOX Racing Shox. ACT[™] Arctic Cat, Arctic Drive System,[™] Arctic Race Suspension,[™] ARS,[™] AWS,[™] Bearcat, C-TEC2,[™] C-TEC4,[™] CatMaster, Cat to the Core,[™] Cross Country,[™] El Tigré, FasTrack, High Country,[™] Lynx, Pantera, Power Claw,[™] ProClimb,[™] ProCross,[™] ProTour,[™] RIDEMORE,[™] Share Our Passion,[™] Slide-Action Rear Suspension,[™] Sno Pro, SpeedRack, Torque Control Link,[™] Twin Spar,[™] World's Fastest Snowmobiles,[™] XT,[™] Z1[™] and ZR are trademarks or registered trademarks of Arctic Cat Inc. Arctic Cat Sales Inc. is not a successor of Arctic Enterprises, Inc. ©2014 Arctic Cat Sales Inc., 601 Brooks Avenue South, Thief River Falls, MN 56701.

At Arctic Cat, we're always improving our snowmobiles to provide the best performance and experience. That's why the specifications for 2015 model Arctic Cat snowmobiles are subject to change without notice. See your dealer for details.

*MSRP excludes tax, license, registration, destination charge of \$400 and dealer setup. Dealer prices may vary.