



2018 Norseman 3000



AVAILABLE COLORS

White

Engine Specifications

Type	4-stroke
Displacement (cc)	700
Cooling	Liquid
Cylinders	2
Bore x Stroke (mm)	76.9 x 75.3
Lubrication	Wet sump
Ignition	Digital controlled coil induction
Engine Stator Output	510 Watts
Fuel Delivery	Electronic Fuel Injected (EFI)
Exhaust	2-into-1 stainless steel pipe with stainless steel muffler
Fuel Capacity gal. (l)	10.7 (40.50)
Oil System Capacity qt. (l)	4.1 (3.88)
Coolant System Capacity qt. (l)	4.8 (4.54)
Minimum Octane	87

Suspension Specifications

Front Suspension	Arctic Race Suspension
Ski Shocks	Arctic Cat IFP 1.5
Front Travel in. (cm)	9.5 (24.13)
Rear Suspension	SLIDE-ACTION Rear Suspension, coupling blocks, Torque-Sensing Link rear arm, adjustable torsion springs
Front Track Shock	Arctic Cat IFP 1.5
Rear Track Shock	Arctic Cat IFP 1.5
Rear Travel in. (cm)	13.5 (34.29)

Dimensions Specifications

Chassis Overall Length in. (cm)	132
Chassis Overall Width in. (cm)	48 (121.92)
Chassis Overall Height in. (cm)	52
Estimated Dry Weight (lbs.)	570
Track Type	Cobra
Track Width in. (cm)	15 (38.1)
Track Length in. (cm)	154
Lug in. (cm)	1.60
Pitch in. (cm)	2.86 (7.26)
Ski Stance in. (cm)	35.5-41.4 (90.17-105.41) Adjustable
Ski Type / Width in. (cm)	ProUte - 10 (25.4)/8 (20.32)
Runner Type	Dual split runner w/carbide

Instrumentation Specifications

Type of Gauge	Power Sport
Speedometer	Digital
Tachometer	Digital
Odometer	Digital
Fuel	Digital
Oil	Indicator Light
Coolant	Digital/Indicator Light
Clock	Digital
Battery Voltage	Digital
Hours	Digital

Feature Specifications

12V Outlet	Standard
Electric Start	Standard
Front Bumper	Sport
Goggle Holder	Accessory
Hand & Thumb Warmers	Standard
Hand Guards	Accessory
Headlights	Dual halogen 2-bulb
Ice Scratchers	Accessory
Lightweight Brake Disc	Accessory
Mirrors	Accessory
Mountain Strap	Standard
Passenger Footrests	Accessory
Passenger Seat	Accessory
Radiator	Standard
Rear Rack	Standard
Rear Storage	Tunnel Bag
Seat	Mountain
Side Panel Wind Deflectors	Accessory
Sno Pro Brake Lever	Accessory
Steering	6.5 in. (16.51 cm) riser with adjustable handlebar and grab strap
Tether Switch	Accessory
Tow Hitch	Pivot
Visor Plug-ins	Accessory
Windshield	14 in. Mid-height

Powertrain Specifications

Drive Clutch	Arctic 6 post (rpm sensing)
Driven Clutch	10.4 in. dia. Arctic (roller cam)
Drive System	Arctic Drive System
Brakes	Race radial master cylinder hydraulic brake
Clutch Calibration ft. (m)	0-5,000 (0-1,524)
Gearing	19/50
Chain Pitch	90
Track Drive Sprocket	8 tooth, 2.86 pitch, exvolute
Reverse	Push-button

All rights reserved. Cobra,[™] Hacksaw[™] and Ripsaw[™] are trademarks of Camoplast Inc. Diamond Direct Drive[™] is a trademark of Black Diamond, Inc. FOX EVOL,[™] FOX FLOAT[™] and FOX Zero Pro are registered trademarks of FOX Racing Shox. ACT[™] Arctic Cat, Arctic Drive System,[™] Arctic Race Suspension,[™] ARS,[™] AWS,[™] Bearcat, C-TEC2,[™] C-TEC4,[™] CatMaster, Cat to the Core,[™] Cross Country,[™] El Tigré, FasTrack,[™] High Country,[™] Lynx,[™] Pantera, Power Claw,[™] ProClimb,[™] ProCross,[™] ProTour,[™] RIDEMORE,[™] Share Our Passion,[™] Slide-Action Rear Suspension,[™] Sno Pro, SpeedRack,[™] Torque Control Link,[™] Twin Spar,[™] World's Fastest Snowmobiles,[™] XT,[™] Z1[™] and ZR are trademarks or registered trademarks of Arctic Cat Inc. Arctic Cat Sales Inc. is not a successor of Arctic Enterprises, Inc. ©2018 Arctic Cat Sales Inc., 601 Brooks Avenue South, Thief River Falls, MN 56701.

At Arctic Cat, we're always improving our snowmobiles to provide the best performance and experience. That's why the specifications for 2019 model Arctic Cat snowmobiles are subject to change without notice. See your dealer for details.

*MSRP excludes tax, license, registration, destination charge of \$400 and dealer setup. Dealer prices may vary.