



2018 Norseman 6000 ES

MSRP \$11,799 USD*

+ Destination Charge: \$400 (\$500 Alaska)



AVAILABLE COLORS

White

Engine Specifications

Type	2-stroke
Displacement (cc)	599
Cooling	Liquid
Cylinders	2
Bore x Stroke (mm)	73.8 x 70
Lubrication	Electronic injection
Ignition	Digitally Controlled CDI
Engine Stator Output	325 Watts
Fuel Delivery	Dual stage injection
Exhaust	APV with tuned pipe, pipe sensor and stainless steel muffler
Fuel Capacity gal. (l)	13.7
Oil System Capacity qt. (l)	3.6
Coolant System Capacity qt. (l)	6.2
Minimum Octane	91

Suspension Specifications

Front Suspension	Arctic Race Suspension
Ski Shocks	Arctic Cat IFP 1.5
Front Travel in. (cm)	9.5 (24.13)
Rear Suspension	XTRA-ACTION Rear Suspension with adjustable torsion springs, and Torque-Sensing Link rear arm
Front Track Shock	Arctic Cat IFP 1.5
Rear Track Shock	Arctic Cat IFP 1.5
Rear Travel in. (cm)	13.5 (34.29)

Dimensions Specifications

Chassis Overall Length in. (cm)	132
Chassis Overall Width in. (cm)	48 (121.92)
Chassis Overall Height in. (cm)	52
Track Type	Cobra
Track Width in. (cm)	15 (38.1)
Track Length in. (cm)	154
Lug in. (cm)	1.60
Pitch in. (cm)	2.86 (7.26)
Ski Stance in. (cm)	35.5-41.4 (90.17-105.41) Adjustable
Ski Type / Width in. (cm)	ProUte - 10 (25.4)/8 (20.32)
Runner Type	Dual split runner w/carbide

Instrumentation Specifications

Type of Gauge	Power Sport
Speedometer	Digital
Tachometer	Digital
Odometer	Digital
Fuel	Digital
Oil	Indicator Light
Coolant	Digital/Indicator Light
Clock	Digital
Battery Voltage	Digital
Hours	Digital

Feature Specifications

12V Outlet	Standard
Electric Start	Standard
Front Bumper	Sport
Goggle Holder	Accessory
Hand & Thumb Warmers	Standard
Hand Guards	Accessory
Headlights	Dual halogen 2-bulb
Ice Scratchers	Accessory
Lightweight Brake Disc	Accessory
Mirrors	Accessory
Mountain Strap	Standard
Passenger Seat	Accessory
Rear Rack	Standard
Rear Storage	Tunnel Bag
Seat	Mountain
Sno Pro Brake Lever	Accessory
Steering	6.5 in. (16.51 cm) riser with adjustable handlebar and grab strap
Tether Switch	Accessory
Tow Hitch	Pivot
Visor Plug-ins	Accessory
Windshield	14 in. Mid-height

Powertrain Specifications

Drive Clutch	TEAM Rapid Response II
Driven Clutch	TEAM Rapid Reaction BOSS
Drive System	Arctic Drive System
Brakes	Race radial master cylinder hydraulic brake
Clutch Calibration ft. (m)	0-5,000 (0-1,524)
Gearing	19/50
Chain Pitch	90
Reverse	Push-button Engine

Specifications Subject To Change

All rights reserved. Cobra,[™] Hacksaw[™] and Ripsaw[™] are trademarks of Camoplast Inc. Diamond Direct Drive[™] is a trademark of Black Diamond, Inc. FOX[®] EVOL,[™] FOX FLOAT[™] and FOX Zero Pro are registered trademarks of FOX Racing Shox. ACT[™] Arctic Cat, Arctic Drive System,[™] Arctic Race Suspension,[™] ARS,[™] AWS,[™] Bearcat, C-TEC2,[™] C-TEC4,[™] CatMaster, Cat to the Core,[™] Cross Country,[™] El Tigré, FasTrack, High Country,[™] Lynx, Pantera, Power Claw,[™] ProClimb,[™] ProCross,[™] ProTour,[™] RIDEMORE,[™] Share Our Passion,[™] Slide-Action Rear Suspension,[™] Sno Pro, SpeedRack, Torque Control Link,[™] Twin Spar,[™] World's Fastest Snowmobiles,[™] XT,[™] Z1[™] and ZR are trademarks or registered trademarks of Arctic Cat Inc. Arctic Cat Sales Inc. is not a successor of Arctic Enterprises, Inc. ©2014 Arctic Cat Sales Inc., 601 Brooks Avenue South, Thief River Falls, MN 56701.

At Arctic Cat, we're always improving our snowmobiles to provide the best performance and experience. That's why the specifications for 2015 model Arctic Cat snowmobiles are subject to change without notice. See your dealer for details.

*MSRP excludes tax, license, registration, destination charge of \$400 and dealer setup. Dealer prices may vary.