

2020 ZR SNO PRO®



Built to thrill on any trail.

- C-TEC2 8000 engine; 165-class HP 2-stroke or C-TEC2 6000 engine; 125-class HP 2-stroke
- New ARS II Front Suspension with Arctic Cat IFP 1.5 ski shocks
- SLIDE-ACTION Rear Suspension with Arctic Cat IFP 2.0
- Standard with electric start

ZR 6000/8000 SNO PRO®	
Color	Charcoal/Green
Engine, Type, Displacement, Cooling, Cylinders (cc)	6000, 2-stroke, 599cc, liquid, 2 cylinder; 8000, 2-stroke, 794cc, liquid, 2 cylinder
Fuel Capacity (gal.), Oil System Capacity (quart)	11.7, 3.25
Drive Clutch	TEAM Rapid Response II
Driven Clutch	TEAM Rapid Reaction BOSS
Front Suspension	ARS II
Rear Suspension	SLIDE-ACTION with 3 wheel rear axle assembly, coupling blocks, Torque-Sensing Link rear arm and adjustable torsion springs
Ski Shocks	Arctic Cat IFP 1.5
Front Track Shock	Arctic Cat IFP 1.5
Rear Track Shock	Arctic Cat IFP 2.0
Chassis Overall Length, Width, Height (in.)	125, 48-49, 48
Track Type	Ripsaw
Track Width, Length, Lug (in.)	15, 137, 1
Ski Stance (in.)	42-43 adjustable
Type of Gauge	Deluxe digital
Starter	Electric push button
Headlights	Dual halogen 2-bulb
Windshield	5.5" race-height
Standard Features	Tunnel bag

WARNING: Arctic Cat snowmobiles can be hazardous to operate. Be sure to read and understand your owner's manual and please pay special attention to the safety instructions. All riders should wear a helmet, eye protection, and protective clothing. Riding and alcohol/drugs don't mix. Never attempt maneuvers beyond your capabilities. Arctic Cat recommends that all riders take a training course. For additional safety and training information, please see your dealer or call 1-800-887-2887. Vehicles shown may include options not included on base model. All materials and specifications are subject to change without notice. ©2020 Textron Specialized Vehicles Inc. All rights reserved. For more information, visit: www.arcticcat.com.